

# ENDURABLE POLISHED CONCRETE SEALER

## TECHNICAL DATA SHEET

- Quick Drying and Quick Curing Industrial Grade Sealer for Concrete
- Incredibly Durable
- Excellent Resistance to Abrasion
- Superior Wearability
- May Be Burnished or Polished to a High Gloss Finish
- Resistant to Chemicals and Water
- Light Traffic in 1 Hour, Heavy Traffic in 2 hours

### CONCENTRATE MIXES 3 PARTS WATER TO 1 PART PRODUCT

Product comes in a concentrate that makes 1 gallon and a concentrate that makes 4 gallons.

ENDURABLE POLISHED CONCRETE SEALER is a low VOC, 6 grams per liter, environmentally safe industrial grade sealer for concrete. This product will harden concrete and can be burnished or polished to a high gloss finish while maintaining excellent slip resistance. This product is quick to dry and cure, provides water and stain resistance, low maintenance—requiring no scrubbing or rinsing. It is non-dusting, non-marking, easy to clean, with high coverage rates between 1000 and 2000 square feet per gallon. It is resistant to water blushing. The product comes in concentrated form and should be diluted 3 parts water to 1 part product.

### **Application Instructions: Apply in thin coats---Apply Evenly---Do not over apply**

Prior to application, product should be mixed thoroughly and all surface contaminants should be removed and the surface completely dry.

Application should be done with a microfiber mop at a rate of 1000-2000 square feet per gallon. After application of sealer is dry, usually 30-45 minutes, the sealer can be burnished or polished with a black strip pad or a hog's hair pad on a high speed burnishing machine. Typically 2 coats are sufficient. It may be used as a maintenance product for repolishing slightly worn traffic areas in commercial applications.

**Do not allow water on the surface for 72 hours.** Subjecting to water prior to 72 hours may result in product turning white. Full cure should be attained in 72 hours. If by accident, water is spilled on surface prior to the 72 hour cure time, soak up water immediately. If the product turns white, let dry completely and then burnish with a black strip pad to remove the whiting. If damage is done during the repair, simply apply another coat of ENDURABLE POLISHED CONCRETE SEALER to damaged area. Regular sweeping, mopping, or mechanical scrubbing with neutral cleaners is recommended for maintenance. Do not use acidic or butyl based cleaners.

KEEP FROM FREEZING-STORE BETWEEN 40 AND 100 DEGREES.

HDIP INC MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of this product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.